

# IMA


## INTEGRATED MOTOR ROD-STYLE ACTUATOR

**ENDURANCE TECHNOLOGY**<sup>SM</sup>  
A Tolomatic Design Principle  
**Patented**



**LINEAR SOLUTIONS MADE EASY**

# The longest lasting, high-force integrated actuator on the market!



The IMA is a compact, durable, high force rod-style actuator. The IMA integrates a servo motor into a ball or roller screw-driven actuator to provide efficient high force in a compact lightweight design envelope. Our patented\* design allows for easy re-lubrication without disassembly for extremely long service life.

\*U.S. PATENT NO. 8,196,484

## The IMA's unique integrated design


### Features:

- Compact, lightweight design
- Long life
- High force
- High positional accuracy
- High efficiency
- Proven performance
- Ratings for extreme environments
- Compatibility
- Low inertia

### Eliminates:

- Couplers
- Adapters
- Belts
- Gears
- Unneeded assembly labor
- Forced air or water cooling
- Hydraulic systems
- Pneumatic systems
- Need for multiple vendors

**PATENTED  
SCREW  
LUBRICATION  
SYSTEM FOR  
EXTENDED  
SERVICE LIFE**



## TOLOMATIC'S ELECTRIC ROD-STYLE ACTUATORS

|                                                                                                             | ERD                                                                                 | RSH                                                                                 | RSA                                                                                 | RSX                                                                                  | GSA                                                                                   | IMA                                                                                   |
|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                                                                                                             |  |  |  |  |  |  |
|                                                                                                             | Rod-Style Actuator                                                                  | Hygienic Rod-Style Actuator                                                         | Rod-Style Actuator                                                                  | Rod-Style Actuator                                                                   | Guided Rod-Style Actuator                                                             | Integrated Servo Actuator                                                             |
| <b>Force</b> up to:                                                                                         | 2.22 kN<br>(500 lbf)                                                                | 35 kN<br>(7,943 lbf)                                                                | 58 kN<br>(13,039 lbf)                                                               | 222.4 kN<br>(50,000 lbf)                                                             | 4.23 kN<br>(950 lbf)                                                                  | 35.8 kN<br>(8,044 lbf)                                                                |
| <b>Speed</b> up to:                                                                                         | 1,016 mm/sec<br>(40 in/sec)                                                         | 498 mm/sec<br>(19.6 in/sec)                                                         | 3,124 mm/sec<br>(123 in/sec)                                                        | 760 mm/sec<br>(29.9 in/sec)                                                          | 3,124 mm/sec<br>(123 in/sec)                                                          | 1,334 mm/sec<br>(52.5 in/sec)                                                         |
| <b>Stroke Length</b> up to:                                                                                 | 609 mm<br>(24 in)                                                                   | 1,219 mm<br>(48 in)                                                                 | 1,524 mm<br>(60 in)                                                                 | 890 mm<br>(35 in)                                                                    | 914 mm<br>(36 in)                                                                     | 457 mm<br>(18 in)                                                                     |
| <b>Screw/Nut Type</b>                                                                                       | Solid, Ball & Roller                                                                | Ball & Roller                                                                       | Solid, Ball & Roller                                                                | Roller                                                                               | Solid & Ball                                                                          | Ball & Roller                                                                         |
| For complete information see <a href="http://www.tolomatic.com">www.tolomatic.com</a> or literature number: |                                                                                     |                                                                                     |                                                                                     |                                                                                      |                                                                                       |                                                                                       |
| <b>Literature Number:</b>                                                                                   | 2190-4000                                                                           | 2100-4010                                                                           | 3600-4166                                                                           | 2171-4001                                                                            | 3600-4166                                                                             | 2700-4000                                                                             |


(Not all models deliver maximum values listed, i.e.: Maximum thrust may not be available with maximum speed)

# IMA - Integrated Motor Actuator

## IMA Applications


### Press Fitting System

- High Force
- Long Life



### Valve / Process Control

- Efficient
- Accurate Positioning
- Quick Response




## CONTENTS

|                                         |       |
|-----------------------------------------|-------|
| What is the IMA? . . . . .              | 2     |
| IMA Applications . . . . .              | 3     |
| IMA Features . . . . .                  | 4     |
| IMA Specs<br>& Performance . . . . .    | 6-10  |
| IMA Dimensions . . . . .                | 11-14 |
| Application Data<br>Worksheet . . . . . | 17    |
| Selection Guidelines . . . . .          | 16    |
| Ordering . . . . .                      | 19    |


### Spot Welding

- Compact, Lightweight
- Repeatable, High Force



### Fluid Dispensing

- Repeatable Force
- Smooth Velocity



### More Applications:

- Aerospace
- Animation
- Assembly
- Automated assembly
- Automatic tool changers
- Automotive
- Clamping
- Converting
- Conveyors
- Cycle testing
- Fillers
- Formers
- Hydraulic replacement
- Laser positioning
- Machine tools
- Material handling systems
- Medical equipment
- Military
- Molding
- Motion simulators
- Open/close doors
- Packaging equipment
- Parts clamping
- Patient lifts
- Pick & place
- Pneumatic replacement
- Precision grinders
- Product test simulations
- Riveting / fastening / joining
- Robot manipulator arms
- Sawmill equipment
- Semiconductor
- Stamping
- Table positioning
- Tension control
- Test stands
- Tube bending
- Volumetric pumps
- Water jet control
- Wave generation
- Web guidance
- Welding
- Wire winding

# IMA INTEGRATED MOTOR ACTUATOR

The IMA is a compact, durable, high force rod-style actuator with an IP65 rating. The IMA integrates a servo motor into a ball or roller screw-driven actuator to provide efficient high force in a compact lightweight design envelope. Our patented design allows for easy re-lubrication without disassembly for extremely long service life. Built-to-order in stroke lengths up to 450 mm (18") with your choice of screw technology.

**ENDURANCE TECHNOLOGY<sup>SM</sup>**  
A Tolomatic Design Principle

## HIGH POSITIONAL ACCURACY

### SCREW ACCURACY

|            |                   |                      |
|------------|-------------------|----------------------|
| Roller Nut | $\pm 0.0004"/ft.$ | $\pm 0.0102mm/300mm$ |
| Ball Nut   | $\pm 0.002"/ft.$  | $\pm 0.051mm/300mm$  |

## REPLACEABLE ROD WIPER

- Prevents contaminants from entering the actuator for extended life

## GREASE PORT

- Screw re-lubrication system provides extended screw service life
- Convenient lubrication without disassembly (IMA22 is lubed for life and does not include grease port)

## INTEGRAL MOUNTING

- Four metric threaded holes on front face are available for direct mounting or addition of customized options

## THREADED ROD END

- Zinc plated alloy steel construction for corrosion resistance
- Provides a common interface to multiple rod end options

## THRUST TUBE

- Steel thrust tube supports extremely high force capabilities
- Salt bath nitride treatment provides excellent corrosion resistance, surface hardness and is very resistant to adherence of weld slag, water and other potential contaminant

## MULTIPLE SCREW TECHNOLOGIES

### YOU CAN CHOOSE:

- Ball screws offer efficiency at a cost effective price
- Roller screws provide the highest force and life ratings available




## INTERNAL BUMPERS

- Bumpers protect the screw and nut assembly from damage at end of stroke

## LIGHTWEIGHT ALUMINUM DESIGN

- Black anodized extrusion design is optimized for rigidity and strength



## ROBOT & DRIVE/CONTROLLER COMPATIBILITY

- Compatible feedback, connector(s) and wiring to match the following robot & drive/controller manufacturers:
  - ABB Robot\*      Techniques FM & NT      • Nachi Robot\*
  - Aerotech BM\*      • Fanuc Robot\*      • Omron\*
  - Allen Bradley MP & VP      • Kawasaki Robot\*      • Parker MPP\*
  - B&R 8LS\*      • Kollmorgen AKM\*      • Schneider Electric SH\*
  - Baldor BSM      • Kuka Robot\*      • SEW CMP\*
  - Beckhoff AM8\*      • Lenze MCA      • Siemens 1F\*
  - Bosch Rexroth MSK      • Motoman / Yaskawa Robot\*      • Stober\*
  - Nidec/Control
- \*Consult Tolomatic for lead time
- Tolomatic standard connector, wiring and flying lead cable can be used to integrate with servo drive manufacturers such as:
  - AMC    • Copley    • Elmo    • + Others
  - STAGGERED CONNECTORS for convenient installation

## HIGH RESOLUTION FEEDBACK

### YOU CAN CHOOSE:

- Incremental encoder
- Multi-turn absolute encoder, Hiperface, Hiperface DSL, EnDat 2.2
- Resolver

## HIGH FORCE ANGULAR CONTACT BEARINGS

- Provides complete support of screw and protects the feedback device from linear forces

## MULTIPLE MOTOR WINDINGS

### YOU CAN CHOOSE:

- 230V or 460V rated windings potted directly into actuator housing
- Skewed motor windings provide minimal torque ripple for smooth linear motion
- Integral thermal switch for over temperature protection
- 1 stack motor (MV21-230V & MV41-460V) available for the IMA22 & IMA33, allows strokes between 3 and 6" providing the force needed for many applications in a more compact, lighter weight packages

## SMOOTH BODY DESIGN

- Eliminates potential contaminant collection points

DISCOVER  
THE  
**IMA-S**  
STAINLESS STEEL  
DESIGN

The best integrated  
hygienic actuator  
available!

CLICK HERE!

## OPTIONS (SEE IMA EXTENDED CATALOG FOR MORE IMA OPTIONS)

### MOUNTING

- Front Face - Standard
- Side Mounting Holes, 2 sides & bottom (no photo)
- Mounting Plates
- Rear Clevis
- Front Flange
- Trunnion, Rear or Front

### ROD END

- Internal Thread - Standard
- External Threads
- Clevis
- Spherical Eye
- Alignment Coupler

### BRAKE

- 24V Spring held / electronically released

### IP67


- For protection against water and dust ingress

### CABLES

- Signal Cable (5 & 10m)
- Power Cable (5 & 10m)

### ARO

- Anti-Rotate



## Performance & Mechanical Specifications:

| SERIES | STACK <sup>1</sup> | NUT/<br>SCREW | SCREW<br>LEAD | DYNAMIC<br>LOAD<br>RATING<br>(1 MIL. REV) | CONT.<br>THRUST | PEAK<br>THRUST | MAX.<br>VELOCITY | BASE<br>INERTIA <sup>2</sup> | INERTIA<br>PER<br>UNIT OF<br>STROKE | BREAK-<br>AWAY<br>TORQUE | NOMINAL<br>BACK DRIVE<br>FORCE <sup>3</sup> |
|--------|--------------------|---------------|---------------|-------------------------------------------|-----------------|----------------|------------------|------------------------------|-------------------------------------|--------------------------|---------------------------------------------|
|        |                    |               | mm            | kN                                        | kN              | kN             | mm/sec           | kg-cm <sup>2</sup>           | kg-cm <sup>2</sup> / mm             | N-m                      | N                                           |
| IMA22  | 1                  | BN05          | 5             | 5.72                                      | 0.89            | 1.45           | 356              | 0.9007                       | 0.00014                             | 0.34                     | 218                                         |
|        | 3                  | BN05          | 5             | 5.72                                      | 1.45            | 1.45           | 356              | 1.4859                       | 0.00014                             | 0.34                     | 218                                         |
|        | 1                  | BN10          | 10            | 4.40                                      | 0.45            | 1.36           | 711              | 0.9007                       | 0.00019                             | 0.34                     | 109                                         |
|        | 3                  | BN10          | 10            | 4.40                                      | 0.80            | 1.45           | 711              | 1.4859                       | 0.00019                             | 0.34                     | 109                                         |
| IMA33  | 1                  | BN05          | 5             | 8.71                                      | 1.62            | 4.45           | 305              | 2.7696                       | 0.00031                             | 0.54                     | 347                                         |
|        | 3                  | BN05          | 5             | 8.71                                      | 4.00            | 4.45           | 292              | 4.8709                       | 0.00031                             | 0.54                     | 347                                         |
|        | 1                  | BN10          | 10            | 5.40                                      | 0.81            | 2.44           | 610              | 2.7908                       | 0.00036                             | 0.54                     | 173                                         |
|        | 3                  | BN10          | 10            | 5.40                                      | 2.00            | 4.00           | 584              | 4.8922                       | 0.00036                             | 0.54                     | 173                                         |
|        | 1                  | BN20          | 20            | 11.39                                     | 0.41            | 1.23           | 1,217            | 3.0003                       | 0.0014                              | 0.54                     | 89                                          |
|        | 3                  | BN20          | 20            | 11.39                                     | 1.00            | 3.00           | 1,167            | 5.2184                       | 0.0014                              | 0.54                     | 89                                          |
|        | 1                  | RN04          | 4             | 41.10                                     | 2.0             | 6.0            | 244              | 2.7835                       | 0.00036                             | 0.60                     | 434                                         |
|        | 3                  | RN04          | 4             | 41.10                                     | 4.7             | 11.1           | 234              | 4.8847                       | 0.00036                             | 0.60                     | 434                                         |
|        | 1                  | RN05          | 5             | 45.42                                     | 1.6             | 4.7            | 305              | 2.7874                       | 0.00041                             | 0.60                     | 347                                         |
|        | 3                  | RN05          | 5             | 45.42                                     | 3.8             | 11.1           | 292              | 4.8937                       | 0.00041                             | 0.60                     | 347                                         |
|        | 1                  | RN10          | 10            | 45.42                                     | 0.8             | 2.3            | 610              | 2.8145                       | 0.00048                             | 0.60                     | 173                                         |
|        | 3                  | RN10          | 10            | 45.42                                     | 1.9             | 5.7            | 584              | 4.9208                       | 0.00048                             | 0.60                     | 173                                         |
| IMA44  | 3                  | BN05          | 5             | 17.95                                     | 7.78            | 10.4           | 267              | 10.0063                      | 0.00209                             | 0.63                     | 405                                         |
|        | 3                  | BN10          | 10            | 15.00                                     | 3.89            | 11.0           | 533              | 10.0459                      | 0.00216                             | 0.63                     | 205                                         |
|        | 3                  | BN25          | 25            | 11.29                                     | 1.56            | 4.7            | 1,334            | 10.3231                      | 0.00265                             | 0.63                     | 80                                          |
|        | 3                  | RN04          | 4             | 56.51                                     | 9.3             | 18.5           | 234              | 9.7764                       | 0.00105                             | 0.70                     | 507                                         |
|        | 3                  | RN05          | 5             | 56.51                                     | 7.3             | 17.1           | 292              | 9.7864                       | 0.00113                             | 0.70                     | 405                                         |
|        | 3                  | RN10          | 10            | 56.51                                     | 3.7             | 11.1           | 584              | 9.8334                       | 0.00122                             | 0.70                     | 205                                         |
| IMA55  | 3                  | BN05          | 5             | 29.87                                     | 13.13           | 17.4           | 167              | 77.9185                      | 0.01757                             | 1.06                     | 681                                         |
|        | 3                  | BN10          | 10            | 33.26                                     | 6.56            | 16.4           | 333              | 78.0428                      | 0.01773                             | 1.06                     | 343                                         |
|        | 3                  | BN20          | 20            | 24.59                                     | 3.28            | 8.21           | 667              | 78.5208                      | 0.01836                             | 1.06                     | 169                                         |
|        | 3                  | RN05          | 5             | 106.06                                    | 12.2            | 35.8           | 201              | 76.6569                      | 0.01273                             | 1.16                     | 676                                         |
|        | 3                  | RN10          | 10            | 106.06                                    | 6.1             | 17.9           | 399              | 76.7962                      | 0.01291                             | 1.16                     | 338                                         |
|        |                    |               | in            | lbf                                       | lbf             | lbf            | in/sec           | lb-in <sup>2</sup>           | lb-in <sup>2</sup> / in             | in-lb                    | lbf                                         |
| IMA22  | 1                  | BN05          | 0.197         | 1,286                                     | 200             | 325            | 14.0             | 0.3078                       | 0.00123                             | 3.0                      | 49                                          |
|        | 3                  | BN05          | 0.197         | 1,286                                     | 325             | 325            | 14.0             | 0.5078                       | 0.00123                             | 3.0                      | 49                                          |
|        | 1                  | BN10          | 0.394         | 989                                       | 102             | 305            | 28.0             | 0.3078                       | 0.00161                             | 3.0                      | 25                                          |
|        | 3                  | BN10          | 0.394         | 989                                       | 180             | 325            | 28.0             | 0.5078                       | 0.00161                             | 3.0                      | 25                                          |
| IMA33  | 1                  | BN05          | 0.197         | 1,958                                     | 365             | 1,000          | 12.0             | 0.9464                       | 0.00266                             | 4.8                      | 78                                          |
|        | 3                  | BN05          | 0.197         | 1,958                                     | 900             | 1,000          | 11.5             | 1.6645                       | 0.00266                             | 4.8                      | 78                                          |
|        | 1                  | BN10          | 0.394         | 1,214                                     | 183             | 549            | 24.0             | 0.9537                       | 0.00313                             | 4.8                      | 39                                          |
|        | 3                  | BN10          | 0.394         | 1,214                                     | 450             | 900            | 23.0             | 1.6717                       | 0.00313                             | 4.8                      | 39                                          |
|        | 1                  | BN20          | 0.788         | 2,560                                     | 92              | 276            | 47.9             | 1.0253                       | 0.01211                             | 4.8                      | 20                                          |
|        | 3                  | BN20          | 0.788         | 2,560                                     | 225             | 675            | 45.9             | 1.7832                       | 0.01211                             | 4.8                      | 20                                          |
|        | 1                  | RN04          | 0.157         | 9,236                                     | 450             | 1,350          | 9.6              | 0.9513                       | 0.00314                             | 5.3                      | 98                                          |
|        | 3                  | RN04          | 0.157         | 9,236                                     | 1,063           | 2,500          | 9.2              | 1.6694                       | 0.00314                             | 5.3                      | 98                                          |
|        | 1                  | RN05          | 0.197         | 10,211                                    | 350             | 1,050          | 12.0             | 0.9525                       | 0.00358                             | 5.3                      | 78                                          |
|        | 3                  | RN05          | 0.197         | 10,211                                    | 850             | 2,500          | 11.5             | 1.6723                       | 0.00358                             | 5.3                      | 78                                          |
|        | 1                  | RN10          | 0.394         | 10,211                                    | 175             | 525            | 24.0             | 0.9618                       | 0.00413                             | 5.3                      | 39                                          |
|        | 3                  | RN10          | 0.394         | 10,211                                    | 425             | 1,275          | 23.0             | 1.6815                       | 0.00413                             | 5.3                      | 39                                          |
| IMA44  | 3                  | BN05          | 0.197         | 4,035                                     | 1,750           | 2,347          | 10.5             | 3.4193                       | 0.01811                             | 5.6                      | 91                                          |
|        | 3                  | BN10          | 0.394         | 3,372                                     | 875             | 2,471          | 21.0             | 3.4329                       | 0.01872                             | 5.6                      | 46                                          |
|        | 3                  | BN25          | 0.985         | 2,537                                     | 350             | 1,049          | 52.5             | 3.5276                       | 0.02303                             | 5.6                      | 18                                          |
|        | 3                  | RN04          | 0.157         | 12,703                                    | 2,100           | 4,150          | 9.2              | 3.3412                       | 0.00917                             | 6.2                      | 114                                         |
|        | 3                  | RN05          | 0.197         | 12,703                                    | 1,650           | 3,850          | 11.5             | 3.3442                       | 0.00984                             | 6.2                      | 91                                          |
| IMA55  | 3                  | RN10          | 0.394         | 12,703                                    | 825             | 2,500          | 23.0             | 3.3602                       | 0.01056                             | 6.2                      | 46                                          |
|        | 3                  | BN05          | 0.197         | 6,714                                     | 2,950           | 3,906          | 6.6              | 26.626                       | 0.15246                             | 9.4                      | 153                                         |
|        | 3                  | BN10          | 0.394         | 7,476                                     | 1,475           | 3,687          | 13.1             | 26.6684                      | 0.15385                             | 9.4                      | 77                                          |
|        | 3                  | BN20          | 0.788         | 5,528                                     | 738             | 1,845          | 26.2             | 26.8318                      | 0.15939                             | 9.4                      | 38                                          |
|        | 3                  | RN05          | 0.197         | 23,843                                    | 2,750           | 8,044          | 7.9              | 26.1949                      | 0.11051                             | 10.3                     | 152                                         |
|        | 3                  | RN10          | 0.394         | 23,843                                    | 1,375           | 4,022          | 15.7             | 26.2425                      | 0.11204                             | 10.3                     | 76                                          |



Performance data was validated using an aluminum face mount plate:  
IMA22 (8.25" x 7.0" x 0.7");  
IMA33 (8.25" x 7.0" x 0.7");  
IMA44 (9.0" x 9.0" x 0.7");  
IMA55 (9.0" x 9.0" x 1.0")  
Ambient Temp. = 77°F (25°C);  
Elevation < 3281' (1,000 m);  
Drive specifications: Sinusoidal Commutation and PWM Voltage Source


<sup>1</sup> Stack winding MV21 / 41  
3 Stack winding MV23 / 43

<sup>2</sup>Value given is for a zero stroke actuator † To be determined, visit [www.tolomatic.com](http://www.tolomatic.com) for up-to-date information

<sup>3</sup>In all vertical application an unpowered IMA will require a brake to maintain position. Tolomatic recommends that the nominal back drive force specification be used for reference only. Back drive force is subject to change throughout the life of the actuator, due to mechanical break in, ambient temperature, and duty cycle variation.

### Reference Only

Back drive force is subject to change throughout the life of the actuator, due to mechanical break in, ambient temperature, and duty cycle variation.



## Performance & Mechanical Specifications:

|                                   |       | IMA22<br>(1 STACK,<br>MV21/41)                                                                              | IMA22<br>(3 STACK,<br>MV23/43) | IMA33<br>(1 STACK,<br>MV21/41) | IMA33<br>(3 STACK,<br>MV23/43) | IMA44          | IMA55          |
|-----------------------------------|-------|-------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|--------------------------------|----------------|----------------|
| FACE SIZE                         | mm    | 63.5                                                                                                        | 63.5                           | 83                             | 83                             | 110            | 142            |
|                                   | in    | 2.5                                                                                                         | 2.5                            | 3.3                            | 3.3                            | 4.4            | 5.6            |
| STROKE                            | mm    | 76.2 to 304.8                                                                                               | 152.4 to 304.8                 | 76.2 to 457.2                  | 152.4 to 457.2                 | 152.4 to 457.2 | 152.4 to 457.2 |
|                                   | in    | 3.0 to 12.0                                                                                                 | 6.0 to 12.0                    | 3.0 to 18.0                    | 6.0 to 18.0                    | 6.0 to 18.0    | 6.0 to 18.0    |
| **BASE WEIGHT                     | kg    | 2.4                                                                                                         | 2.9                            | 5.2                            | 6.4                            | 13             | 24.8           |
|                                   | lb    | 5.3                                                                                                         | 6.4                            | 11.4                           | 14.1                           | 28.6           | 54.5           |
| WEIGHT PER UNIT<br>OF STROKE      | kg/mm | 0.0073                                                                                                      | 0.0073                         | 0.0118                         | 0.0118                         | 0.0197         | 0.03771        |
|                                   | lb/in | 0.2428                                                                                                      | 0.2428                         | 0.6603                         | 0.6603                         | 1.1035         | 2.1115         |
| SCREW LEAD<br>ACCURACY            | BN    | in/ft = 0.002    mm/300 = 0.051 (0.004 in/ft for IMA33BN20 and IMA44BN25)                                   |                                |                                |                                |                |                |
|                                   | RN    | in/ft = 0.0004    mm/300 = 0.010                                                                            |                                |                                |                                |                |                |
| SCREW LEAD<br>BACKLASH            | BN    | in = 0.004    mm = 0.1                                                                                      |                                |                                |                                |                |                |
|                                   | RN    | in = 0.0020    mm = 0.051                                                                                   |                                |                                |                                |                |                |
| TEMP RANGE                        | °C    | Standard: 10 to 40; Extended: -20 to 60 (Contact Tolomatic if operation in the Extended Range is required)  |                                |                                |                                |                |                |
|                                   | °F    | Standard: 50 to 104; Extended: -4 to 140 (Contact Tolomatic if operation in the Extended Range is required) |                                |                                |                                |                |                |
| IP RATING                         |       | Standard IP65, Optional IP67 (Static)                                                                       |                                |                                |                                |                |                |
| REL. HUMIDITY<br>(NON-CONDENSING) |       | 5 to 90%                                                                                                    |                                |                                |                                |                |                |
| SHOCK                             |       | 20g peak, 6 msec duration                                                                                   |                                |                                |                                |                |                |
| VIBRATION                         |       | 2.5g 30....2,000 Hz                                                                                         |                                |                                |                                |                |                |

\*In vertical applications an unpowered IMA will require a brake to maintain position if the load on the actuator exceeds this value

\*\*Value given is for a zero stroke actuator


## Motor Specifications:

| Motor Specifications:                 |                  | IMA22 |      |      |      | IMA33 |      |       |      | IMA44 |       | IMA55 |      |
|---------------------------------------|------------------|-------|------|------|------|-------|------|-------|------|-------|-------|-------|------|
| WINDING/MOTOR VOLTAGE                 |                  | MV21  | MV41 | MV23 | MV43 | MV21  | MV41 | MV23  | MV43 | MV23  | MV43  | MV23  | MV43 |
| TORQUE<br>CONSTANT (K <sub>t</sub> )  | N-m/A Peak       | 0.37  | 0.74 | 0.49 | 0.93 | 0.61  | 1.21 | 0.62  | 1.21 | 0.61  | 1.20  | 0.76  | 1.51 |
|                                       | in-lb/A Peak     | 3.3   | 6.6  | 4.3  | 8.2  | 5.4   | 10.7 | 5.5   | 10.7 | 5.4   | 10.6  | 6.7   | 13.4 |
| VOLTAGE<br>CONSTANT (K <sub>e</sub> ) | V/Krpm Peak      | 51    | 102  | 61   | 122  | 81    | 160  | 79.8  | 154  | 78.1  | 153.1 | 100   | 201  |
|                                       |                  |       |      |      |      |       |      |       |      |       |       |       |      |
| CONTINUOUS<br>STALL TORQUE            | N-m              | 0.85  | 0.85 | 1.50 | 1.50 | 1.8   | 1.8  | 4.4   | 4.3  | 8.4   | 8.5   | 12.7  | 12.7 |
|                                       | in-lb            | 7.5   | 7.5  | 13.3 | 13.3 | 16    | 16   | 39    | 38   | 74    | 75    | 112   | 112  |
| CONTINUOUS<br>STALL CURRENT           | A <sub>RMS</sub> | 1.6   | 0.8  | 2.2  | 1.15 | 2.1   | 1.1  | 5     | 2.5  | 9.7   | 5     | 11.8  | 5.9  |
|                                       |                  |       |      |      |      |       |      |       |      |       |       |       |      |
| PEAK TORQUE                           | N-m              | 2.54  | 2.54 | 4.5  | 4.5  | 5.4   | 5.4  | 13.2  | 12.9 | 25.1  | 25.4  | 31.6  | 31.6 |
|                                       | in-lb            | 22.5  | 22.5 | 39.9 | 39.9 | 48    | 48   | 117   | 114  | 222   | 225   | 280   | 280  |
| PEAK CURRENT                          | A <sub>RMS</sub> | 4.8   | 2.4  | 6.6  | 3.45 | 6.3   | 3.3  | 15    | 7.5  | 29.1  | 15    | 29.5  | 14.8 |
| RESISTANCE                            | Ohms             | 18.1  | 72.4 | 7.1  | 28.3 | 10    | 40.1 | 2.07  | 8.3  | 0.58  | 2.32  | 0.57  | 2.93 |
| INDUCTANCE                            | mH               | 10.7  | 42   | 4.5  | 18   | 13.6  | 54.1 | 3.8   | 15   | 2.75  | 11.5  | 1.4   | 5.8  |
| BUS VOLTAGE                           | V <sub>RMS</sub> | 230   | 460  | 230  | 460  | 230   | 460  | 230   | 460  | 230   | 460   | 230   | 460  |
| SPEED @ RATED V                       | RPM              | 4,264 |      |      |      | 3,650 |      | 3,500 |      | 3,500 |       | 2,400 |      |
| NO. OF POLES                          |                  | 8     |      |      |      |       |      |       |      |       |       |       |      |



RoHS Compliant Components;



Performance data was validated using an aluminum face mount plate: IMA22/33 (8.25" x 7.0" x 0.7"); IMA44 (9.0" x 9.0" x 0.7"); IMA55 (9.0" x 9.0" x 1.0"); Ambient Temperature = 77°F (25°C); Elevation < 3281' (1,000 m); Drive specifications: Sinusoidal Commutation and PWM Voltage Source




## CRITICAL SPEED




## SCREW BUCKLING LOAD


### Ball Screw



### Roller Screw




All curves represent properly lubricated and maintained actuators.



## LIFE

### BALL SCREW

### ROLLER SCREW



All curves represent properly lubricated and maintained actuators.

NOTE: The  $L_{10}$  expected life of a ball screw linear actuator is expressed as the linear travel distance that 90% of properly maintained ball screw manufactured are expected to meet or exceed. This is not a guarantee and this graph should be used for estimation purposes only.

The underlying formula that defines this value is:

$$L_{10} = \left( \frac{C}{P_e} \right)^3 \cdot \ell \equiv$$

$L_{10}$  Travel life in millions of units (in or mm),  
where:

$C$  = Dynamic load rating (lbf) or (N)

$P_e$  = Equivalent load (lbf) or (N)

If load is constant across all movements then:

actual load = equivalent load

$\ell$  = Screw lead (in/rev) (mm/rev)

Use the "Equivalent Load" calculation below, when the load is not constant throughout the entire stroke. In cases where there is only minor variation in loading, use greatest load for life calculations.

$$P_e = \sqrt[3]{\frac{L_1(P_1)^3 + L_2(P_2)^3 + L_3(P_3)^3 + L_n(P_n)^3}{L}}$$

Where:

$P_e$  = Equivalent load (lbf) or (N)

$P_n$  = Each increment at different load (lbf) or (N)

$L$  = Total distanced traveled per cycle (extend + retract stroke)

$[L = L_1 + L_2 + L_3 + L_n]$

$L_n$  = Each increment of stroke at different load (in) or (mm)



## RE-LUBRICATION RECOMMENDATION:

**IMA33, IMA44, IMA55:** IMA Lubrication requirements for electric actuators depend on the motion cycle (velocity, force, duty cycle), type of application, ambient temperature, environmental surrounding and various other factors.

For many general purpose applications, Tolomatic ball screw actuators are typically considered lubricated for life unless otherwise specified, such as those actuator models outfitted with a re-lubrication feature. For roller screw or ball screw actuators outfitted with a re-lubrication feature, Tolomatic recommends to re-lubricate the actuator at least once per year or every 1,000,000 cycles, whichever comes first, to maximize service life. For more demanding applications such as pressing, high frequency or other highly stressed applications, the re-lubrication interval for these actuators will vary and will need to be more frequent. In these demand-

ing applications, it is recommended to execute at least 5 full stroke moves every 5,000 cycles of operation (or more frequent if possible) to re-distribute the grease within the actuator.


Re-lubricate with Tolomatic Grease #2744-9099 into the grease zerk located on the rod end.

| Quantity                   |                                        |    |
|----------------------------|----------------------------------------|----|
| IMA33                      | $2.5 + [0.010 \times L \text{ (mm)}]$  | g  |
| IMA44                      | $4.8 + [0.010 \times L \text{ (mm)}]$  | g  |
| IMA55                      | $6.6 + [0.019 \times L \text{ (mm)}]$  | g  |
| IMA33                      | $0.09 + [0.009 \times L \text{ (in)}]$ | oz |
| IMA44                      | $0.17 + [0.009 \times L \text{ (in)}]$ | oz |
| IMA55                      | $0.23 + [0.017 \times L \text{ (in)}]$ | oz |
| L=stroke length (mm or in) |                                        |    |



**⚠** In some applications oil may leak from the grease zerk. In contamination sensitive applications replace grease zerk with plug.

## SIDE LOAD CONSIDERATIONS

The IMA integrated motor actuator is not meant to be used in applications where side loading occurs. Loads must be guided and supported. Loads should be aligned with the line of motion of the thrust rod. Side loading will affect the life of the actuator.



### IMA SIDE LOAD SPECIFICATIONS



USE THE TOLOMATIC SIZING  
AND SELECTION SOFTWARE  
AVAILABLE ON-LINE AT


[www.tolomatic.com](http://www.tolomatic.com) OR...

CALL TOLOMATIC AT 1-800-328-2174.

We will provide any assistance needed to determine the proper actuator for the job.

## BRAKE CONSIDERATIONS

In all vertical application an un-powered IMA will require a brake to maintain position. Tolomatic recommends that the nominal back drive force specification (listed on page IMA\_8) be used for reference only. Back drive force is subject to change throughout the life of the actuator, due to mechanical break in, ambient temperature, and duty cycle variation.



See "P" dimension, pg. 11

A brake can be used with the actuator to keep it from backdriving, typically in vertical applications. A brake may be used for safety reasons or for energy savings allowing the actuator to hold position when un-powered. See page IMA\_23 for ordering information.

NOTE: The optional Spring-Applied / Electronically-Released Brake requires 24V power. Input current rating:

IMA22 - 0.35 Amps;  
IMA33 - 0.43 Amps;  
IMA44 - 0.67 Amps;  
IMA55 - 0.66 Amps.


### Brake Specifications:

| SERIES         |                    | IMA22 | IMA33 | IMA44 | IMA55 |
|----------------|--------------------|-------|-------|-------|-------|
| ROTOR INERTIA  | gm-cm <sup>2</sup> | 19    | 73    | 239   | 214   |
|                | oz-in <sup>2</sup> | 0.104 | 0.400 | 1.307 | 1.171 |
| CURRENT        | Amp                | 0.35  | 0.43  | 0.67  | 0.66  |
| HOLDING TORQUE | N-m                | 1.6   | 4.0   | 9.0   | 16.4  |
|                | in-lb              | 14    | 35    | 89    | 145   |
| ENGAGE TIME    | mSec               | 75    | 40    | 25    | 15    |
| DISENGAGE TIME | mSec               | 20    | 50    | 35    | 25    |
| VOLTAGE        | Vdc                | 24    |       |       |       |



## Dimensions: All Sizes

## DIMENSIONS



|     | IMA22     | IMA33      | IMA44     | IMA55      |
|-----|-----------|------------|-----------|------------|
| A   | 25.38     | 30.13      | 38.08     | 57.13      |
| B   | —         | 28.3       | 32.3      | 41.9       |
| C   | 48.000    | 60.000     | 72.000    | 100.000    |
| D   | 54.00     | 69.00      | 85.00     | 110.00     |
| E   | M6 x 1.0  | M8 x 1.25  | M8 x 1.25 | M12 x 1.75 |
| F   | 13.2      | 14.5       | 17.1      | 22.5       |
| G   | 20.00     | 36.00      | 55.00     | 65.00      |
| H   | M8 x 1.25 | M12 x 1.25 | M20 x 1.5 | M27 x 2.0  |
| J   | 16.5      | 22.2       | 25.9      | 38.1       |
| K   | 1.5       | 1.5        | 1.5       | 1.5        |
| L   | 17.3      | 17.3       | 16.8      | 24.1       |
| M   | 109.8     | 153.7      | 200.0     | 266.2      |
| N   | 1.5       | 1.5        | 1.5       | 1.5        |
| P1  | 41.2      | 44.2       | 44.2      | 48.2       |
| P2  | 86.7      | 80.8       | 80.0      | 96.8       |
| P3  | —         | 50.3       | 50.3      | 54.3       |
| P4  | —         | 93.5       | 89.0      | 96.8       |
| P5  | 41.2      | 44.2       | 44.2      | 59.9       |
| P6  | 86.7      | 80.8       | 80.0      | 96.8       |
| P7  | 58.7      | 59.2       | 59.2      | 67.5       |
| P8  | 96.3      | 100.6      | 99.1      | 111.5      |
| P9  | 65.1      | 59.2       | 63.6      | 80.5       |
| P10 | 107.2     | 100.6      | 99.1      | 122.9      |
| Q   | 63.5      | 83.6       | 110.5     | 143.6      |
| R   | 40.000    | 50.000     | 75.000    | 100.000    |
| S1  | 104.4     | 124.6      | 151.4     | 184.3      |
| S2  | 102.0     | 122.2      | 149.0     | 181.9      |
| S3  | —         | 113.5      | 140.4     | 173.3      |
| T   | 63.5      | 83.6       | 110.5     | 143.6      |
| U   | M6 x 1.0  | M8 x 1.25  | M8 x 1.25 | M12 x 1.75 |
| V   | 13.5      | 16.5       | 16.5      | 20.5       |
| W   | 9.5       | 16.8       | 22.2      | 22.2       |
| X   | 9.5       | 16.8       | 22.2      | 22.2       |
| Y   | 27.3      | 30.4       | 30.4      | 34.4       |
| Z   | 60.6      | 73.1       | 77.9      | 86.9       |
| AA  | 70.00     | 92.00      | 127.00    | 155.00     |
| BB  | 128.6     | 172.5      | 218.3     | 291.8      |

Dimensions in millimeters

|     | IMA22  | IMA33  | IMA44  | IMA55 |
|-----|--------|--------|--------|-------|
| A   | 0.999  | 1.186  | 1.499  | 2.249 |
| B   | —      | 1.11   | 1.27   | 1.65  |
| C   | 1.8898 | 2.3622 | 2.8346 | 3.937 |
| D   | 2.126  | 2.717  | 3.346  | 4.331 |
| E   | —      | —      | —      | —     |
| F   | 0.52   | 0.57   | 0.68   | 0.89  |
| G   | 0.787  | 1.417  | 2.165  | 2.559 |
| H   | —      | —      | —      | —     |
| J   | 0.65   | 0.88   | 1.02   | 1.50  |
| K   | 0.06   | 0.06   | 0.06   | 0.06  |
| L   | 0.68   | 0.68   | 0.66   | 0.95  |
| M   | 4.32   | 6.05   | 7.88   | 10.48 |
| N   | 0.06   | 0.06   | 0.06   | 0.06  |
| P1  | 1.62   | 1.74   | 1.74   | 1.90  |
| P2  | 3.41   | 3.18   | 3.15   | 3.81  |
| P3  | —      | 1.98   | 1.98   | 2.14  |
| P4  | —      | 3.68   | 3.50   | 3.81  |
| P5  | 1.62   | 1.74   | 1.74   | 2.36  |
| P6  | 3.41   | 3.18   | 3.15   | 3.81  |
| P7  | 2.31   | 2.33   | 2.33   | 2.66  |
| P8  | 3.79   | 3.96   | 3.90   | 4.39  |
| P9  | 2.56   | 2.33   | 2.50   | 3.17  |
| P10 | 4.22   | 3.96   | 3.90   | 4.84  |
| Q   | 2.50   | 3.29   | 4.35   | 5.66  |
| R   | 1.5748 | 1.9685 | 2.9528 | 3.937 |
| S1  | 4.11   | 4.91   | 5.96   | 7.26  |
| S2  | 4.02   | 4.81   | 5.87   | 7.16  |
| S3  | —      | 4.47   | 5.53   | 6.82  |
| T   | 2.50   | 3.29   | 4.35   | 5.66  |
| U   | —      | —      | —      | —     |
| V   | 0.53   | 0.65   | 0.65   | 0.80  |
| W   | 0.38   | 0.66   | 0.88   | 0.88  |
| X   | 0.38   | 0.66   | 0.88   | 0.88  |
| Y   | 1.08   | 1.20   | 1.20   | 1.35  |
| Z   | 2.39   | 2.88   | 3.07   | 3.42  |
| AA  | 2.756  | 3.622  | 5.000  | 6.102 |
| BB  | 5.06   | 6.79   | 8.6    | 11.49 |

Dimensions in inches

|      |         |                                                         |
|------|---------|---------------------------------------------------------|
| P1 = | Dx1 D1N | Digital Encoder                                         |
| P2 = | Dx1 D1B | Digital Encoder with Brake                              |
| P3 = | DE2 D1N | *Digital Encoder (Nidec/Control Techniques NT)          |
| P4 = | DE2 D1B | *Digital Encoder (Nidec/Control Techniques NT) w/ Brake |
| P5 = | Dx1 R1N | Resolver                                                |
| P6 = | Dx1 R1B | Resolver with Brake                                     |

|       |          |                                              |
|-------|----------|----------------------------------------------|
| P7 =  | Dx1A1N   | SICK Hipurface                               |
|       | DA2A2N   | SICK Hipurface DSL                           |
| P8 =  | Dx1A1B   | SICK Hipurface w/ Brake                      |
|       | DA2A2B   | SICK Hipurface DSL w/ Brake                  |
| P9 =  | Dx1 H4N  | Heidenhain Endat 2.2                         |
| P10 = | Dx1 H4B  | Heidenhain Endat 2.2 w/ Brake                |
| S1 =  | DT1, DE1 | Tolomatic Standard, Nidec/Control Techniques |
|       | DL1, DS1 | FM, Lenze, Siemens                           |


## KEY FEATURES: 1-STACK & 3-STACK MOTORS

### IMA22

| SERIES      | MV21/41 | MV23/43       |
|-------------|---------|---------------|
| STROKE      | mm      | 76.2 to 304.8 |
|             | in      | 3.0 to 12.0   |
| PEAK THRUST | N       | up to 1,446   |
|             | lbf     | up to 325     |

### IMA33

| SERIES      | MV21/41 | MV23/43       |
|-------------|---------|---------------|
| STROKE      | mm      | 76.2 to 457.2 |
|             | in      | 3.0 to 18.0   |
| PEAK THRUST | N       | up to 4,673   |
|             | lbf     | up to 1,050   |





|                                                                                       |     |                                    |
|---------------------------------------------------------------------------------------|-----|------------------------------------|
| S2 =                                                                                  | DB1 | Bosch MSK Motor Series             |
| S3 =                                                                                  | DE2 | Nidec/Control Techniques NT Series |
| *Uses Box Mount Connectors (IP67 not available)<br>Not available as standard on IMA22 |     |                                    |





## Dimensions: Rod End Options



### EXTERNAL THREADED ROD END (MET)





### CLEVIS ROD END (RCL)





### SPHERICAL ROD EYE (SRE)




### ALIGNMENT COUPLER (ALC + MET)



### ALIGNMENT COUPLER FEMALE (ALC) \*



\*For IMA44 & IMA55 Only



|   | IMA22      | IMA33     | IMA44     | IMA55      |
|---|------------|-----------|-----------|------------|
| A | M10 x 1.25 | M16 x 1.5 | M20 x 1.5 | M27 x 2.0  |
| B | 22.1       | 34.3      | 41.4      | 38.1       |
| C | 24.6       | 37.3      | 44.5      | 50.8       |
| D | 17.3       | 17.3      | 16.8      | 24.1       |
| E | 10.00      | 16.00     | 20.00     | 30.00      |
| F | 10.0       | 16.0      | 20.0      | 30.0       |
| G | 20.0       | 32.0      | 40.0      | 55.0       |
| H | 45.0       | 72.0      | 90.0      | 123.5      |
| J | 9.1        | 13.2      | 14.2      | 10.1       |
| K | 2.5        | 3.0       | 3.0       | 5.1        |
| L | 10.00      | 16.00     | 20.00     | 30.00      |
| M | 48.0       | 72.0      | 87.0      | 123.5      |
| N | 14.0       | 21.0      | 25.0      | 37.0       |
| P | 12.5       | 15.0      | 18.0      | 25.0       |
| Q | 5.0        | 8.0       | 10.0      | 13.5       |
| R | 53.0       | 76.0      | 82.0      | 93.0       |
| S | 20.0       | 32.0      | 40.0      | 54.0       |
| T | M10 x 1.25 | M16 x 1.5 | M20 x 1.5 | M27 x 2.0  |
| U | 30.0       | 41.0      | 42.0      | 55.0       |
| V | —          | —         | 11.0      | 11.0       |
| W | —          | —         | 4.1       | 2.4        |
| X | —          | —         | M20 x 1.5 | M27 x 1.75 |
| Y | —          | —         | 42.0      | 54.0       |

Dimensions in millimeters

|   | IMA22 | IMA33 | IMA44 | IMA55 |
|---|-------|-------|-------|-------|
| A | —     | —     | —     | —     |
| B | 0.87  | 1.35  | 1.63  | 1.80  |
| C | 0.97  | 1.47  | 1.75  | 2.00  |
| D | 0.68  | 0.68  | 0.66  | 0.95  |
| E | 0.394 | 0.630 | 0.787 | 1.181 |
| F | 0.39  | 0.63  | 0.79  | 1.18  |
| G | 0.79  | 1.26  | 1.57  | 2.17  |
| H | 1.77  | 2.83  | 3.54  | 4.86  |
| J | 0.36  | 0.52  | 0.56  | 0.40  |
| K | 0.10  | 0.12  | 0.12  | 0.20  |
| L | 0.394 | 0.630 | 0.787 | 1.181 |
| M | 1.89  | 2.84  | 3.43  | 4.86  |
| N | 0.55  | 0.83  | 0.98  | 1.46  |
| P | 0.49  | 0.59  | 0.71  | 0.94  |
| Q | 0.20  | 0.32  | 0.39  | 0.53  |
| R | 2.09  | 2.99  | 3.23  | 3.66  |
| S | 0.79  | 1.26  | 1.57  | 2.16  |
| T | —     | —     | —     | —     |
| U | 1.18  | 1.61  | 1.65  | 2.17  |
| V | —     | —     | 0.43  | 0.43  |
| W | —     | —     | 0.16  | 0.09  |
| X | —     | —     | —     | —     |
| Y | —     | —     | 1.65  | 2.13  |


Dimensions in inches




## Dimensions: Mounting Options

## DIMENSIONS

### FRONT FLANGE MOUNT (FFG)




### FRONT TRUNNION MOUNT (TRF)



|    | IMA22               | IMA33  | IMA44  | IMA55                |
|----|---------------------|--------|--------|----------------------|
| A  | 11.2                | 15.0   | 16.0   | 17.8                 |
| B  | 67.3                | 87.0   | 110.5  | 150.0                |
| C  | 100.00              | 126.00 | 150.00 | 230.00               |
| D  | 117.3               | 150.0  | 170.0  | 260.0                |
| E  | 50.00               | 63.00  | 75.00  | 115.00               |
| F  | 8.7                 | 12.3   | 14.7   | 16.7                 |
| G  | 11.99               | 15.98  | 19.99  | 24.99                |
| H  | 11.96               | 15.95  | 19.96  | 24.97                |
| J  | 8.6                 | 16.0   | 20.1   | 24.9                 |
| K  | 68.0                | 90.0   | 123.0  | 160.0                |
| L  | 10.9                | 19.2   | 26.3   | 33.1                 |
| M  | 63.5                | 83.6   | 110.5  | 143.6                |
| N  | 15.0                | 15.0   | 21.0   | 28.0                 |
| Q  | 26.000 <sup>1</sup> | 32.000 | 50.000 | 60.000               |
| R  | 45.000 <sup>2</sup> | 60.000 | 90.000 | 110.000 <sup>4</sup> |
| S  | 10.000 <sup>3</sup> | 12.000 | 16.000 | 20.000 <sup>5</sup>  |
| T  | 20.00               | 24.00  | 36.00  | 40.00                |
| U  | 13.00               | 16.00  | 22.00  | 27.00                |
| V  | 11.99               | 15.98  | 19.99  | 24.99                |
| W  | 11.96               | 15.95  | 19.96  | 24.97                |
| X  | 8.6                 | 16.0   | 20.1   | 24.9                 |
| Y  | 68.0                | 90.0   | 123.0  | 160.0                |
| Z  | 10.9                | 19.2   | 26.3   | 33.1                 |
| AA | 63.5                | 83.6   | 110.5  | 143.6                |
| BB | 15.0                | 20.0   | 25.0   | 32.0                 |


Dimensions in millimeters

### REAR CLEVIS MOUNT (PCD)



|   |                   |
|---|-------------------|
| 1 | +0.520mm/-0.000mm |
| 2 | +0.000mm/-0.620mm |
| 3 | +0.036mm/-0.000mm |
| 4 | +0.000mm/-0.870mm |
| 5 | +0.052mm/-0.000mm |

### REAR TRUNNION MOUNT (TRR)



|   |                   |
|---|-------------------|
| 1 | +0.0205"/-0.0000" |
| 2 | +0.0000"/-0.0244" |
| 3 | +0.0014"/-0.0000" |
| 4 | +0.0000"/-0.0343" |
| 5 | +0.0020"/-0.0000" |



Dimensions in inches

|    | IMA22               | IMA33  | IMA44  | IMA55               |
|----|---------------------|--------|--------|---------------------|
| A  | 0.44                | 0.59   | 0.63   | 0.70                |
| B  | 2.65                | 3.43   | 4.35   | 5.91                |
| C  | 3.937               | 4.961  | 5.906  | 9.055               |
| D  | 4.62                | 5.91   | 6.69   | 10.24               |
| E  | 1.969               | 2.480  | 2.953  | 4.528               |
| F  | 0.34                | 0.48   | 0.58   | 0.66                |
| G  | 0.472               | 0.629  | 0.787  | 0.984               |
| H  | 0.471               | 0.628  | 0.786  | 0.983               |
| J  | 0.34                | 0.63   | 0.79   | 0.98                |
| K  | 2.68                | 3.54   | 4.84   | 6.30                |
| L  | 0.43                | 0.76   | 1.04   | 1.30                |
| M  | 2.50                | 3.29   | 4.35   | 5.66                |
| N  | 0.59                | 0.59   | 0.83   | 1.10                |
| Q  | 1.0236 <sup>1</sup> | 1.2598 | 1.9685 | 2.3622              |
| R  | 1.7717 <sup>2</sup> | 2.3622 | 3.5433 | 4.3307 <sup>4</sup> |
| S  | 0.3937 <sup>3</sup> | 0.4724 | 0.6299 | 0.7874 <sup>5</sup> |
| T  | 0.787               | 0.945  | 1.417  | 1.575               |
| U  | 0.512               | 0.630  | 0.866  | 1.063               |
| V  | 0.472               | 0.629  | 0.787  | 0.984               |
| W  | 0.471               | 0.628  | 0.786  | 0.983               |
| X  | 0.34                | 0.63   | 0.79   | 0.98                |
| Y  | 2.68                | 3.54   | 4.84   | 6.30                |
| Z  | 0.43                | 0.76   | 1.04   | 1.30                |
| AA | 2.50                | 3.29   | 4.35   | 5.66                |
| BB | 0.59                | 0.79   | 0.98   | 1.26                |





## Dimensions: Options


### SIDE MOUNTING (MST)




### MOUNTING PLATES (MP2)



### ANTI ROTATE (ARO)



|    | IMA22 | IMA33 | IMA44 | IMA55 |
|----|-------|-------|-------|-------|
| mm | 7.6   | 11.4  | 13.0  | 11.2  |
| in | 0.30  | 0.45  | 0.51  | 0.44  |



|   | IMA22    | IMA33     | IMA44     | IMA55      |
|---|----------|-----------|-----------|------------|
| A | 67.8     | 100.7     | 143.0     | 191.2      |
| B | 20.0     | 21.0      | 25.0      | 30.0       |
| C | 34.00    | 44.00     | 50.00     | 85.00      |
| D | M6 X 1.0 | M8 x 1.25 | M8 x 1.25 | M12 x 1.75 |
| E | 13.1     | 14.5      | 17.1      | 22.5       |
| F | 67.8     | 100.7     | 143.0     | 191.2      |
| G | 20.0     | 21.0      | 25.0      | 30.0       |
| H | 80.00    | 102.00    | 130.00    | 170.00     |
| J | 100.0    | 125.0     | 155.0     | 200.0      |
| K | 11.0     | 12.7      | 12.7      | 20.0       |
| L | 30.0     | 38.1      | 38.1      | 50.0       |
| M | 15.0     | 19.1      | 19.1      | 0.5        |
| N | 8.7      | 10.7      | 10.7      | 15.1       |
| P | 12.7     | 15.9      | 19.8      | 31.8       |
| Q | 43.3     | 57.0      | 70.5      | 95.1       |
| R | 51.2     | 69.7      | 83.2      | 109.7      |
| S | 34.8     | 38.1      | 45.9      | 68.2       |
| T | 46.2     | 62.7      | 62.7      | 106.7      |
| U | 81.0     | 105.2     | 108.5     | 142.5      |
| V | 9.5      | 12.7      | 12.7      | 19.1       |
| W | 65.0     | 89.0      | 93.0      | 115.6      |
| X | 16.1     | 16.1      | 15.5      | 22.8       |
| Y | 54.9     | 72.3      | 85.7      | 118.3      |

Dimensions in millimeters

|   | IMA22 | IMA33 | IMA44 | IMA55 |
|---|-------|-------|-------|-------|
| A | 2.67  | 3.97  | 5.63  | 7.53  |
| B | 0.79  | 0.83  | 0.98  | 1.18  |
| C | 1.339 | 1.732 | 1.969 | 3.346 |
| D | —     | —     | —     | —     |
| E | 0.52  | 0.57  | 0.68  | 0.89  |
| F | 2.67  | 3.97  | 5.63  | 7.53  |
| G | 0.79  | 0.83  | 0.98  | 1.18  |
| H | 3.150 | 4.016 | 5.118 | 6.693 |
| J | 3.94  | 4.92  | 6.10  | 7.87  |
| K | 0.43  | 0.50  | 0.50  | 0.79  |
| L | 1.18  | 1.50  | 1.50  | 1.97  |
| M | 0.59  | 0.75  | 0.75  | 0.98  |
| N | 0.34  | 0.42  | 0.42  | 0.59  |
| P | 0.50  | 0.63  | 0.78  | 1.25  |
| Q | 1.71  | 2.24  | 2.78  | 3.74  |
| R | 2.02  | 2.75  | 3.28  | 4.32  |
| S | 1.37  | 1.50  | 1.81  | 2.69  |
| T | 1.82  | 2.47  | 2.47  | 4.20  |
| U | 3.19  | 4.14  | 4.27  | 5.60  |
| V | 0.38  | 0.50  | 0.50  | 0.75  |
| W | 2.56  | 3.50  | 3.66  | 4.55  |
| X | 0.63  | 0.63  | 0.61  | 0.90  |
| Y | 2.16  | 2.85  | 3.38  | 4.66  |

Dimensions in inches

# The IMA is matched to your drive/controller choice

**The IMA has been successfully integrated with the following servo drive/controller and robot companies:**

#### Controller/ Drive Manufacturers

- Aerotech BM\*
- Allen Bradley MP & VP
- B&R 8LS\*
- Baldor BSM
- Beckhoff AM8\*
- Bosch Rexroth MSK
- Kollmorgen AKM\*
- Lenze MCA
- Nidec/Control Techniques FM & NT
- Omron\*
- Parker MPP\*
- Schneider Electric SH\*
- SEW CMP\*
- Siemens 1F
- Stober\*
- Others

#### Robot Manufacturers

- ABB\*
- Fanuc\*
- Kawasaki\*
- Kuka\*
- Motoman\*
- Nachi\*
- Others

\* Consult Tolomatic for lead time

Contact Tolomatic if your preferred servo drive/controller or robot supplier is not listed above.




Licensed  
Partner

For additional information regarding the integration of the IMA to an Allen Bradley/Rockwell drive see tech note linked below:


[3600-4187 TN IMA-AB-servo.pdf](#)



## The IMA is the most rigorously tested Tolomatic product yet



Cutting edge products like the IMA don't just fall into place. Over 20,000 hours of testing were required to prove the design that ships today. Thermal imaging, dynamic loading and other state-of-the-art techniques give us the confidence to stand behind our published performance data.



## Selection Guidelines

### 1 ESTABLISH MOTION PROFILE

Using the application stroke length, desired cycle time and loads establish the motion profile details.

### 2 COMPARE OPERATING (PEAK) THRUST AND SPEED TO OPERATING REGION

Calculate the application required operating (peak) thrust and speed and compare to tables on pages IMA\_6-7. The calculated thrust and speed must fall within the operating region of the actuator.

### 3 COMPARE SEVERE DUTY (CONTINUOUS) THRUST AND SPEED TO SEVERE DUTY REGION

Calculate the RMS thrust and speed required and compare to tables on pages IMA\_6-7. The calculated thrust and speed must fall within the severe duty region. See complete instructions on page IMA\_10 for help calculating continuous force.

$$T_{RMS} = \sqrt{\frac{\sum (T_i^2 \times t_i)}{\sum (t_i)}} \quad V_{RMS} = \sqrt{\frac{\sum (V_i^2 \times t_i)}{\sum (t_i)}}$$

### 4 CONSIDER SCREW/NUT CHOICES

Choose roller nuts for its longer life (see Life graph on page IMA\_9) and higher peak loads. Ball nuts are cost competitive and more efficient (see table on page IMA\_6).

#### SCREW ACCURACY

|            |               |                  |
|------------|---------------|------------------|
| Roller Nut | ± 0.0004"/ft. | ± 0.0102mm/300mm |
| Ball Nut   | ± 0.002"/ft.  | ± 0.051mm/300mm  |

### 5 VERIFY CRITICAL SPEED OF THE SCREW

Verify that the application's peak linear velocity does not exceed the critical speed value for the size and lead of the screw selected.

### 6 VERIFY AXIAL BUCKLING STRENGTH OF THE SCREW (ROLLER SCREW)

Verify that the peak thrust does not exceed the critical buckling force for the size of the screw selected.

### 7 MOTOR WINDINGS & VOLTAGES

Choose motor windings optimized for 230 Vac and 460 Vac voltage busses. The 1 stack motor (MV21-230V & MV41-460V), available for the IMA22/33, allows strokes between 3 and 6" providing the thrust needed for many applications in a more compact, lighter weight package

### 8 CALCULATE LUBRICATION INTERVAL

See page IMA\_10 for an overview and IMA Users Guide (#2700-4001) for complete instructions to calculate lubrication interval.

### 9 TEMPERATURE

The IMA is intended to operate in an environment with an ambient temperature between 50-104°F, (10-40°C). Performance should be de-rated if the ambient temperature is above 77°F (25°C). Contact the factory if the ambient temperature does not fit within this range. NOTE: Temperature of the actuator's body can approach 180°F

(82°C) in aggressive applications. Adequate clearance to ensure actuator's ambient conditions do not rise drastically should be allowed.

### 10 BRAKE CONSIDERATIONS

In all vertical application an unpowered IMA will require a brake to maintain position. Tolomatic recommends that the nominal back drive force specification be used for reference only. Back drive force is subject to change throughout the life of the actuator, due to mechanical break in, ambient temperature, and duty cycle variation.

A brake can be used with the actuator to keep it from back-driving, typically in vertical applications. A brake may be used for safety reasons or for energy savings allowing the actuator to hold position when unpowered. See page IMA\_19 for ordering information.

NOTE: The optional Spring-Applied/Electronically Released Brake requires 24V power. Input current rating:  
IMA22 - 0.35 Amps; IMA33 - 0.43 Amps;  
IMA44 - 0.67 Amps; IMA55 - 0.66 Amps.

### 11 CHOOSE MOTOR CONNECTORS & FEEDBACK DEVICE

Connector choice and wiring emulates popular motor manufacturers for compatibility.

Current connector choices include:

- Bosch Rexroth MSK Series
- Control Techniques FM & NT
- Lenze MCA Series

Current feedback choices include:

- Incremental Encoder
- Absolute Encoder, Hiperface, Hiperface DSL, EnDat 2.2
- Resolver

Contact Tolomatic for additional motor connectors, feedback combinations and motor files for third party drives.

### 12 CONSIDER MOUNTING & ROD END OPTIONS

Examine mounting options dimensional drawings on page IMA\_11-14. Standard mounting on the IMA are 4 tapped holes on the front rod end face of the actuator. The Side Mount option (MST) includes 12 tapped holes, 4 on each side and 4 on the bottom of the actuator. Other fixed mounting options are the Front Flange Mount (FFG) and Mounting Plates (MP2). Pivoting mount options are Front Trunnion (TRF), Rear Trunnion (TRR) and Rear Clevis Mount (PCD).

Rod End Options include: External Threaded Rod End (MET), Clevis Rod End (RCL), Spherical Rod Eye (SRE) and Alignment Coupler (ALC).

NOTE: Regardless of the mounting option chosen, care must be taken to ensure that the load is guided and in-line with the thrust rod's line of motion. Misalignment of the thrust rod's line of motion will cause degradation in the actuator's expected life.


### 13 CONSIDER ENVIRONMENTAL RATING AND ANTI-ROTATE OPTIONS

The environmental rating for a standard IMA is IP65, choose IP67 for protection against water and dust ingress. Choose the Anti-Rotate Option (ARO) if required. Call Tolomatic at 1-800-328-2174 for help in determining the best actuator for your application.

# APPLICATION DATA WORKSHEET


Fill in known data. Not all information is required for all applications

sizeit.tolomatic.com  
for fast, accurate  
actuator selection




## ORIENTATION


☐ Horizontal



☐ Vertical



☐ Incline °



☐ Load supported by actuator OR ☐ Load supported by other mechanism

## MOVE PROFILE

### EXTEND

Move Distance \_\_\_\_\_

☐ inch ☐ millimeters

Move Time \_\_\_\_\_ sec

Max. Speed \_\_\_\_\_

☐ in/sec ☐ mm/sec

Dwell Time After Move \_\_\_\_\_ sec

### RETRACT

Move Distance \_\_\_\_\_

☐ inch ☐ millimeters

Move Time \_\_\_\_\_ sec

Max. Speed \_\_\_\_\_

☐ in/sec ☐ mm/sec

Dwell Time After Move \_\_\_\_\_ sec

## NO. OF CYCLES

☐ per minute ☐ per hour

## HOLD POSITION?

☐ Required

☐ Not Required

☐ After Move

☐ During Power Loss

## STROKE LENGTH

order in  
mm ONLY

☐ millimeters (S M)  
(Metric)

**NOTE:** If load or force changes during cycle use the highest numbers for calculations

### EXTEND

#### LOAD

☐ lb ☐ kg  
(U.S. Standard) (Metric)

#### FORCE

☐ lbf ☐ N  
(U.S. Standard) (Metric)

### RETRACT

#### LOAD

☐ lb ☐ kg  
(U.S. Standard) (Metric)

#### FORCE

☐ lbf ☐ N  
(U.S. Standard) (Metric)

## PRECISION

Repeatability \_\_\_\_\_


☐ inch ☐ millimeters

## OPERATING ENVIRONMENT

Temperature, Contamination, Water, etc.

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

## MOTION PROFILE



Graph your most demanding cycle, including accel/decel, velocity and dwell times. You may also want to indicate load variations and I/O changes during the cycle. Label axes with proper scale and units.

## CONTACT INFORMATION

Name, Phone, Email  
Co. Name, Etc.

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_



USE THE TOLOMATIC SIZING AND SELECTION SOFTWARE AVAILABLE ON-LINE AT [www.tolomatic.com](http://www.tolomatic.com) OR... CALL TOLOMATIC AT 1-800-328-2174. We will provide any assistance needed to determine the proper actuator for the job.

EMAIL [help@tolomatic.com](mailto:help@tolomatic.com)

# IMA - Integrated Motor Actuator

## Replacement Option Parts Ordering

| PART NO.  | DESCRIPTION                                 |
|-----------|---------------------------------------------|
| 2722-9014 | Spherical Rod Eye Kit, IMA22                |
| 2733-9014 | Spherical Rod Eye Kit, IMA33                |
| 2744-9014 | Spherical Rod Eye Kit, IMA44                |
| 2755-9014 | Spherical Rod Eye Kit, IMA55                |
| 2722-9015 | Clevis Rod End Kit, IMA22                   |
| 2733-9015 | Clevis Rod End Kit, IMA33                   |
| 2744-9015 | Clevis Rod End Kit, IMA44                   |
| 2755-9015 | Clevis Rod End Kit, IMA55                   |
| 2124-1070 | Alignment Coupler Kit, IMA22                |
| 2132-1060 | Alignment Coupler Kit, IMA33                |
| 2150-1060 | Alignment Coupler Kit, IMA44                |
| 2164-1060 | Alignment Coupler Kit, IMA55                |
| 2722-9010 | Mounting Plate Kit, IMA22                   |
| 2733-9010 | Mounting Plate Kit, IMA33                   |
| 2744-9010 | Mounting Plate Kit, IMA44                   |
| 2755-9010 | Mounting Plate Kit, IMA55                   |
| 2722-9018 | Front Flange Mount Kit, IMA22               |
| 2733-9018 | Front Flange Mount Kit, IMA33               |
| 2744-9018 | Front Flange Mount Kit, IMA44               |
| 2755-9018 | Front Flange Mount Kit, IMA55               |
| 2722-2045 | Rear Clevis Mount, IMA22                    |
| 2733-1045 | Rear Clevis Mount, IMA33                    |
| 2744-1045 | Rear Clevis Mount, IMA44                    |
| 2755-1045 | Rear Clevis Mount, IMA55                    |
| 2722-9075 | Anti Rotate, Bearing Assy, IMA22            |
| 2733-9075 | Anti Rotate, Bearing Assy, IMA33 & 44       |
| 2755-9075 | Anti Rotate, Bearing Assy, IMA55            |
| 2722-9074 | Anti Rotate, Shaft Clamp Assy, IMA22        |
| 2722-2211 | Anti Rotate, Shaft, IMA22 - Indicate Stroke |
| 2733-9074 | Anti Rotate, Shaft Clamp Assy, IMA33        |

| PART NO.  | DESCRIPTION                                         |
|-----------|-----------------------------------------------------|
| 2733-1211 | Anti Rotate, Shaft, IMA33 - Indicate Stroke         |
| 2744-9074 | Anti Rotate, Shaft Clamp Assy, IMA44                |
| 2744-1211 | Anti Rotate, Shaft, IMA44 - Indicate Stroke         |
| 2755-9074 | Anti Rotate, Shaft Clamp Assy, IMA55                |
| 2755-1211 | Anti Rotate, Shaft, IMA55 - Indicate Stroke         |
| 2733-1611 | Motor Power Cable, M23, 6 Pin, 5m, 460V AC          |
| 2733-1612 | Motor Power Cable, M23, 6 Pin, 5m, 460V AC, Brake   |
| 2733-1613 | Encoder Cable, M23, 12 Pin, 5m, Resolver/ Absolute  |
| 2733-1614 | Encoder Cable, M23, 17 Pin, 5m, Incremental         |
| 2744-1488 | Motor Power Cable, M23, 6 Pin, 5m, 230V AC          |
| 2744-1489 | Motor Power Cable, M23, 6 Pin, 5m, 230V AC, Brake   |
| 2733-1221 | Motor Power Cable, M23, 6 Pin, 10m, 460V AC         |
| 2733-1222 | Motor Power Cable, M23, 6 Pin, 10m, 460V AC, Brake  |
| 2733-1223 | Encoder Cable, M23, 12 Pin, 10m, Resolver/ Absolute |
| 2733-1224 | Encoder Cable, M23, 17 Pin, 10m, Incremental        |
| 2744-1221 | Motor Power Cable, M23, 6 Pin, 10m, 230V AC         |
| 2744-1222 | Motor Power Cable, M23, 6 Pin, 10m, 230V AC, Brake  |
| 2744-1016 | Mobilith SHC220 Grease (Ball nut/screw)             |
| 2744-9099 | Grease (Roller nut/screw)                           |
| 2552-1132 | Wiper, IMA22                                        |
| 2115-1030 | Wiper, IMA33                                        |
| 2744-1003 | Wiper, IMA44                                        |
| 2140-1030 | Wiper, IMA55                                        |
| 2744-1213 | Zerk Cap                                            |
| 2744-9092 | Kit, Zerk with Cap                                  |
| 2744-1214 | Grease Ftg. Plug                                    |

All parts are listed for REPLACEMENT ONLY. If not ordered on original unit the IMA may require additional tapped holes or replacement rod end. Contact Tolomatic.

\*Not valid with DA2A2X option

[tolomatic.com/ask](http://tolomatic.com/ask)  
Technical support  
before and after  
purchase



# IMA - Integrated Motor Actuator

## Ordering

MODEL SELECTION (MUST BE IN THIS ORDER)

IMA 44 BN05 SM304-8 MV23 DT1D1 N ALC MP2 IP67 CR5

### MODEL

IMA Integrated Motor Actuator

### SIZE

22 22 Series Actuator  
33 33 Series Actuator  
44 44 Series Actuator  
55 55 Series Actuator

### NUT/SCREW

Screw/Nut combinations available

| 22   | 33   | 44   | 55   | Description            |
|------|------|------|------|------------------------|
| BN05 | BN05 | BN05 | BN05 | Ball Nut, 5 mm lead    |
| BN10 | BN10 | BN10 | BN10 | Ball Nut, 10 mm lead   |
| —    | BN20 | —    | BN20 | Ball Nut, 20 mm lead   |
| —    | —    | BN25 | —    | Ball Nut, 25 mm lead   |
| —    | RN04 | RN04 | —    | Roller Nut, 4 mm lead  |
| —    | RN05 | RN05 | RN05 | Roller Nut, 5 mm lead  |
| —    | RN10 | RN10 | RN10 | Roller Nut, 10 mm lead |

### STROKE LENGTH

SM ——— Stroke, (76.2 to 457.2) enter stroke length in millimeters

*NOTE: Maximum stroke for IMA22 is 12" (304.8 mm)*

### MOTOR VOLTAGE

MV21\* 230 Vac, Motor Voltage, 1 Stack Winding  
MV41\* 460 Vac, Motor Voltage, 1 Stack Winding  
MV23 230 Vac, Motor Voltage, 3 Stack Winding  
MV43 460 Vac, Motor Voltage, 3 Stack Winding

*\*NOTE: 22/33 size actuators only*

OPTIONS (IN ANY ORDER)

### BRAKE OPTION

N NO Brake  
B Brake

### ROD END OPTIONS

— Standard, female, internally threaded rod end  
MET Male Externally Threaded Rod End  
SRE Spherical Eye Rod End  
RCL Clevis Rod End  
ALC Alignment Coupler\*  
*\*NOTE: For IMA44 & IMA55 Only ALC (Alignment Coupler) requires ARO (Anti-Rotate) for proper operation*

### MOUNTING OPTIONS

— Standard Face Mount  
MP2 Mounting Plates - 2 req.  
FFG Front Flange Mount  
TRF Trunnion Mount, Front  
TRR Trunnion Mount, Rear  
PCD Clevis Mount, Rear  
MST Side Mount (tapped holes on 3 sides)

### OTHER OPTIONS

IP67\*\* Ingress Protection Rating  
ARO Anti Rotate  
LUB Food Grade Grease  
*\*\*IP67 is not available with DE2 (Control Techniques NT connectors) Not available on any IMA22*

### CABLES

**Tolomatic standard**  
CR5 6m flying lead cables, power and feedback  
**Tolomatic standard**  
CR10 10m flying lead cables, power and feedback  
For custom cable lengths please contact Tolomatic. Lead times will vary.  
*\*NOTE: only use these cable options with DT1 motor connector, use cables from drive manufacturer for all others.*  
For IP rated cables contact Tolomatic

| MOTOR SERIES CONNECTORS   | FEEDBACK DEVICE       |
|---------------------------|-----------------------|
| Allen Bradley MP DA1      | A1 SICK Hiperface     |
| Allen Bradley VP DA2      | A2 SICK Hiperface DSL |
| Bosch Rexroth MSK DB1     | A1 SICK Hiperface     |
| Nidec/Cntl. Tech., FM DE1 | A1 SICK Hiperface     |
| Nidec/Cntl. Tech., FM DE1 | R1 Resolver           |
| Nidec/Cntl. Tech., FM DE1 | D1 Incremental        |
| Nidec/Cntl. Tech., NT DE2 | D1 Incremental        |
| Lenze MCS DL1             | A1 SICK Hiperface     |
| Lenze MCS DL1             | R1 Resolver           |
| Lenze MCS DL1             | D1 Incremental        |

| MOTOR SERIES CONNECTORS                         | FEEDBACK DEVICE         |
|-------------------------------------------------|-------------------------|
| Siemens 1F DS1                                  | H4 Heidenhain Endat 2.2 |
| Tolomatic Standard DT1                          | D1 Incremental          |
| Tolomatic Standard DT1                          | R1 Resolver             |
| Tolomatic Standard DT1                          | A1 SICK Hiperface       |
| Tolomatic Standard DT1                          | H1 Heidenhain Endat 2.2 |
| Motor Connector or Feedback Device Not Shown DX | ***See below            |

\*\*\* Tolomatic can configure the IMA to connect to a drive using cables from other leading drive manufacturers including but not limited to those listed below.

|          |            |                    |        |
|----------|------------|--------------------|--------|
| ABB      | Fanuc      | Motoman            | SEW    |
| Aerotech | Kawasaki   | Nachi              | Stober |
| B&R      | Kollmorgen | Omron              | Others |
| Baldor   | Kuka       | Parker             |        |
| Beckhoff | Lenze      | Schneider Electric |        |

This integration includes customer specified motor thermal protection, feedback, connectors, flying lead/connectorized extension cables and motor alignment.

For more information about combinations not listed above, or other customizations, contact Tolomatic.



[tolomatic.com/CAD](http://tolomatic.com/CAD)  
Download 3D CAD  
Always use CAD solid model to determine critical dimensions



[tolomatic.com/ask](http://tolomatic.com/ask)  
Technical support  
before and after purchase

# The Tolomatic Difference Expect More From the Industry Leader:




## INNOVATIVE PRODUCTS

Solutions with Endurance Technology<sup>SM</sup> for challenging applications.



## FAST DELIVERY

Built-to-order with configurable stroke lengths and flexible mounting options.



## ACTUATOR SIZING

Size and select electric actuators with our online software.



## YOUR MOTOR HERE<sup>®</sup>

Match your motor to compatible mounting plates with Tolomatic actuators.




## CAD LIBRARY

Download 2D or 3D CAD files for Tolomatic products.



## TECHNICAL SUPPORT

Get a question answered or request a virtual design consultation with one of our engineers.



**ServoWeld<sup>®</sup> Actuators**  
**Electric Linear Actuators**

**Pneumatic Actuators**  
**Power Transmission Products**



**MADE IN U.S.A.**

**Tolomatic<sup>TM</sup>**  
**EXCELLENCE IN MOTION**

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV  
= ISO 9001 =  
Certified site: Hamel, MN

### USA - Headquarters

#### Tolomatic Inc.

3800 County Road 116  
Hamel, MN 55340, USA  
**Phone:** (763) 478-8000  
Toll-Free: **1-800-328-2174**  
sales@tolomatic.com  
[www.tolomatic.com](http://www.tolomatic.com)

### MEXICO

#### Centro de Servicio

Parque Tecnológico Innovación  
Int. 23, Lateral Estatal 431,  
Santiago de Querétaro,  
El Marqués, México, C.P. 76246  
**Phone:** +1 (763) 478-8000  
help@tolomatic.com

### EUROPE

#### Tolomatic Europe GmbH

Elisabethenstr. 20  
65428 Rüsselsheim  
Germany  
**Phone:** +49 6142 17604-0  
help@tolomatic.eu  
[www.tolomatic.com/de-de](http://www.tolomatic.com/de-de)

### CHINA

#### Tolomatic Automation Products (Suzhou) Co. Ltd.

No. 60 Chuangye Street, Building 2  
Huqiu District, SND Suzhou  
Jiangsu 215011 - P.R. China  
**Phone:** +86 (512) 6750-8506  
Tolomatic\_China@tolomatic.com

All brand and product names are trademarks or registered trademarks of their respective owners. Information in this document is believed accurate at time of printing. However, Tolomatic assumes no responsibility for its use or for any errors

that may appear in this document. Tolomatic reserves the right to change the design or operation of the equipment described herein and any associated motion products without notice. Information in this document is subject to change without notice.

Visit [www.tolomatic.com](http://www.tolomatic.com) for the most up-to-date technical information